

## Flash PPN DDR Memory Model

### Overview

Memory is a major part of every electronic product. Every system on chip (SoC) contains embedded memories and must also interface with external memory components. The operation of these interfaces impacts both SoC functionality and performance, making memory interface verification a crucial step in the SoC development process.

Cadence® Memory Models are the gold standard for memory interface verification. Used by more than 500 customers, Cadence Memory Models provide support for 6,500 memories spanning 60 memory interface types and 85 memory manufacturers.



### Vendor Certification

Memory models for commercial memory components are based on the manufacturer's datasheets and are then provided to the manufacturer for certification. This closed-loop quality control process means that you can trust your simulation results. Models for new external memory standards that do not yet have commercial component providers and models for internal memory standards are based upon the specifications provided by the controlling standards body, such as JEDEC, ONFi, and SD Association. Cadence works closely with our early-adopter customers to ensure the quality of these models.

### Accurate Timing Analysis

When memory models represent actual memory chips and modules, the memory models include full timing parameters that support accurate gate-level simulations. Timing specs are conveniently displayed in the PureView tool and can be overridden for what-if analysis.

### Second Source Evaluation

Memory models are inserted into a testbench as generic models that are then associated with a personality file to represent a specific component. This makes it easy to do second-source evaluation of memory components.

---

## Specification Support

The model supports all versions of E2NAND (Hynix) and EFNAND (Samsung), the latest being version 3.0.

---

## Key Features

- All three modes of device operation supported through dynamic configuration
  - CRC can be enabled for data transfer in the DDR mode dynamically
  - Communication with the device can be tested by write/read to scratch pad
  - The complementary pins for DQS/RE can be enabled dynamically
  - The program error lists can be cleared and controller status 'pending program error bit' reset (to 0)
- 



Cadence Design Systems enables global electronic design innovation and plays an essential role in the creation of today's electronics. Customers use Cadence software, hardware, IP, and expertise to design and verify today's mobile, cloud, and connectivity applications. [www.cadence.com](http://www.cadence.com)

© 2014 Cadence Design Systems, Inc. All rights reserved worldwide. Cadence and the Cadence logo are registered trademarks of Cadence Design Systems, Inc. in the United States and other countries. All rights reserved. All other trademarks are the property of their respective owners.